

532,180

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/041099 A1

(51) International Patent Classification⁷: **A61B 17/28,**
B25B 7/16

CH-2503 Biel (CH). **BRÖNIMANN**, Urs [CH/CH]; Rue
Centrale 115, CH-2503 Biel (CH).

(21) International Application Number:
PCT/CH2003/000718

(74) Agent: **LIEBETANZ, Michael**; Isler & Pedrazzini AG,
Gotthardstrasse 53, Postfach 6940, CH-8023 Zürich (CH).

(22) International Filing Date:
3 November 2003 (03.11.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE
(utility model), DE, DK (utility model), DK, DM, DZ, EC,
EE (utility model), EE, EG, ES, FI (utility model), FI, GB,
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL,
PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL,
SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02405938.8 4 November 2002 (04.11.2002) EP

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (*for all designated States except US*):
STRYKER TRAUMA SA [CH/CH]; Bohnackerweg
1, CH-2545 Selzach (CH).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **KEBEL, Roland**
[CH/CH]; Bohnackerweg 1, CH-2545 Selzach (CH).
RUSCH, Christoph [CH/CH]; Rue Centrale 115,

[Continued on next page]

(54) Title: ORTHOPAEDIC RATCHETING FORCEPS



(57) Abstract: An orthopaedic ratcheting forceps, especially for fixation of fractures, comprises two handles (2, 12), wherein a first catching element (5) is mounted pivotally with one handle (2 or 12) and wherein a complementary catching element (25) is mounted on the other handle (12 or 2). The forceps can assume only two stable settings which can be switched with a single hand, one closed setting within which the jaws (4) of the forceps can only be further closed and an open setting within which the handles (2, 12) of the forceps are freely movable, so that the forceps can be opened as well as closed. In one handle (12) a leaf spring (28) is provided and biased between two mounting points (27; 13) which spring (28) is mounted between abutting side walls (14, 24) within said handle (12). Furthermore a lever end (25) connected with one of the catching elements (26) engages the spring (28) and through movement of the activation element (32) the lever end (25) and/or the spring (28) is switchable between the closed setting and the open setting.

WO 2004/041099 A1



Declaration under Rule 4.17:

- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*

Orthopaedic ratcheting forceps

5 The invention relates to an orthopaedic ratcheting forceps and specifically to a forceps used to manipulate and hold the bone for fixation of fractures.

The prior art shows a multitude of manipulating devices for use during orthopaedic surgery. An exemplary forceps according to the preamble of the main claim of this invention is shown in WO 89/06939 (U.S. Patent No. 4,896,665). Beside the fact of the possibility to interchange tips of the forceps as shown in said application, another important practical point for the surgeon is the possibility to change the attack point of the forceps, i.e. to have a reversible ratchet mechanism. The advantage of the ratchet according to said PCT application resides in the fact, as shown in Fig. 9, 8 and 9, that through switching a lever through three switching positions the forceps can move freely (Fig. 9, neutral position) or in either direction (Fig. 10 or Fig. 11, respectively). Although this approach facilitates the work of the surgeon, it has been found not to be entirely satisfactory. The mechanism is difficult to manipulate with only one hand.

25

Another known forceps is disclosed in US 5,674,244. The pliers according to this document have the advantage that almost all of the ratcheting structure is within the handles and do not extend beyond the outer form of the instrument. There is provided a spring to exert the counter-force to open the pliers, when the release button is pushed. The advantage of reduced dimensions of the forceps goes with the practical disadvantage in activating the locking device of the pliers between the handles.

30

In view of this prior art the object of the invention is to provide an orthopaedic ratcheting forceps for a surgeon giving him better control for the locking device and at the same time
5 strengthen the security of the pliers.

This object is achieved for a forceps through the features of claim 1 or claim 7.

10 Further objects and advantages are achieved through the features of the subclaims and exemplary embodiments of the invention are disclosed in the following description in which:

Fig. 1 is a view in side elevation of a forceps according to a first embodiment of the invention with the locking device
15 in an open setting,

Fig. 2 is an enlarged view of the lever portion within circle II in Fig. 1,

Fig. 3 is an enlarged view of the locking portion within circle III in Fig. 1,

20 Fig. 4 is a view in side elevation of the forceps according to Fig. 1 with the locking device in a closed setting,

Fig. 5 is an enlarged view of the lever portion within circle V in Fig. 4,

Fig. 6 is an enlarged view of the locking portion within circle
25 VI in Fig. 4,

Fig. 7 is a view in side elevation of a forceps according to a second embodiment of the invention with the locking device in an open setting,

Fig. 8 is an enlarged view of the lever portion within circle VI
30 in Fig. 7,

Fig. 9 is an enlarged view of the locking portion within circle VII in Fig. 7,

Fig. 10 is a view in side elevation of the forceps according to

Fig. 5 with the locking device in a closed setting,
Fig. 11 is an enlarged view of the lever portion within circle IX
in Fig. 10,
Fig. 12 is an enlarged view of the locking portion within circle
5 X in Fig. 10,
Fig. 13 is a view in side elevation of a forceps according to a
third embodiment of the invention with the locking device
in an open setting, and
Fig. 14 is a view in side elevation of the forceps according to
10 Fig. 13 with the locking device in a closed setting.

Fig. 1 shows a view in side elevation of a forceps 1 according
to a first embodiment of the invention with the locking device
in an open setting, i.e. in a setting in which the handles 2 and
15 12 are freely movable about an pivot point 3. The forceps 1 has
jaws 4 comprising sharp points provided to enter into bone mate-
rial and/or surgical plates and bone material. It is clear that
other configurations may be chosen, e.g. that the jaws comprise
internal teeth.

20

On the inner side of handle 2, a shaped rod 5 is pivotally
mounted by means of a pin 6. A leaf spring 7 pushes the rod 5
from the outer side of the handle 2 into the direction or to-
wards the pivot point 3. In a more simple embodiment the spring
25 7 may be omitted, especially if the guiding bore 8 (not shown)
within the second handle 12 is sufficiently narrow. The rod 5
comprises a number of catching elements or ratchet teeth 10.
These may comprise grooves in a transversal direction to the
longitudinal axis of the slightly curved rod 5. The rod 5 is
30 preferably slightly curved, having a radius of curvature equiva-
lent to the distance from the pivot point 3. The grooves or
notches (=catching elements 10) are provided on the inside of
the rod 5, i.e. directed towards the pivot point 3.

As mentioned above, within the second handle a guiding bore 8 is located with e.g. rectangular dimensions to accommodate the rectangular rod 5. If the rod 5 is more or less round then the guiding bore 8 may be cylindrical, or a rounded slit etc. .

The second handle 12 comprises a second pivot point 13 in the neighborhood of the bore 8, dividing the handle 12 in one fingerhole part 32 and in one jaw part 22, hinged together at said second pivot point 13. This allows for a locking structure 20 to be mounted between the first and second pivot points 3 and 13, respectively, of the handle 12. The jaw part 22 of the second handle 12, nearby the pivot point 13, splits of in two arms 14 and 24 between which the end 25 of the fingerhole part 32 is located. The two arms 14 and 24 join together in one end point which may advantageously be in the vicinity of the pivot point 13. Said end 25 can be moved between the inner sides of the arms 14 and 24. In the position of Fig. 1 where end 25 is positioned toward arm 14 a nose 26 integrally, mounted on fingerhole handle part 32, is free and does not engage the catching elements 10 of rod 5.

Between two end points (27 and here pivot point 13) of the arms 14 and 24, respectively, is provided a leaf spring 28. Leaf spring 28 engages the end 25 of fingerhole part 32 and is part of the lever and locking mechanism of the ratchet. In the preferred embodiment, spring 25 is made of spring steel and supplies sufficient force to maintain the nose 26 into engagement with the teeth of arm 5 when deflected towards arm 24.

30

Fig. 2 is an enlarged view of the lever portion within circle II in Fig. 1. Same features in all drawings always have the same reference numerals. Spring 28 is mounted with the transversal

direction of the leaf perpendicular to the drawing plane and therefore parallel to the axes of the pivot points 3 and 13. Therefore two noses 29 provided parallel one to another and encompassing the leaf spring 28 are mounted on the end 25 and extending into the space between the arms 14 and 24 provide guiding means for the spring 28. Since the spring 28 is biased, i.e. longer than the length of a direct line between the end points 27 and 13 of the arms 14 and 24, the end 25 can only take two stable positions, one open setting according to Fig. 1 (deflected towards arm 14) and one closed setting according to Fig. 3 (deflected towards arm 24). The noses 29 may be small bolts or cylinders with enough play between them to allow the movement of the spring 28. The surface of the bolts 29 on the opposite side to the position of the spring 28 can be directly used to abut against the arm 14 or arm 24, respectively.

Fig. 3 is an enlarged view of the locker portion within circle III in Fig. 1. The teeth 10 comprise two different slopes 70, 71. Slope 71, which is the slope oriented towards fixation point 6, is more or less perpendicular to the current longitudinal axis of rod 5. The other slope 70 is inclined in direction of fixation point 6 with an angle between preferably 30 and 60 degrees in comparison to the direction of slope 71.

Fig. 4 shows a view in side elevation of the forceps 1 according to Fig. 1 with the locking device in a closed setting, i.e. in a setting in which the handles 2 and 12 are only movable about the pivot point 3 in a direction closing the jaws 4 of the forceps 1. Fig. 5 is an enlarged view of the lever portion within circle V in Fig. 4. As can be seen in comparison of the two settings of the forceps in Fig. 1 and 4, the handles 2 and 12 are freely movable (i.e. they can be opened). There can be an additional spring, not shown in Fig. 1 and 4, between handles 2 and 12 in

the vicinity of pivot point 3, urging the handles 2 and 12 apart. Otherwise (without said spring) the forceps may be opened by the surgeon as he would do with scissors. Upon pushing the handle 12 and especially the fingerhole part 32 towards the other fingerhole part 42, a moment is exerted upon the spring 28 through the lever provided through second pivot point 13 and the lever length to the end 25. This moment pushes the spring 28 out of the stable open setting as shown in Fig. 1 towards the second stable setting as shown in Fig. 4, the closed setting. Through the movement of the fingerhole part 32 relative to the jaws part 22 of the handle 21 the nose 26 engages one of the catching elements 10 of rod 5. Therefore upon releasing the fingerhole parts 32 and 42, a counter pressure upon the jaws 4 of forceps 1 will not open the handles 2 and 12 because the forceps 1 is in a stable closed setting. However, the surgeon has the possibility to further close the fingerhole parts 32 and 42. To ensure the possibility of this movement the catching elements 10 of rod 5 and the nose 26 are formed asymmetrically, ensuring that the nose 26 can glide from one catching element 10 to the next one which is nearer to the pivot point 6 while forbidding the inverse movement.

The surgeon can also very easily release the grip of the forceps through pushing the fingerhole 32 apart from the fingerhole 42, disengaging the nose 26 from the catching elements 10, when the setting according to Fig. 1 is reached. This means that he controls the opening and closing of the forceps 1 through simple manipulation and relative movement of the fingerhole parts 32 and 42. There is no need for a separate switch, button or release mechanism.

Fig. 6 is an enlarged view of the locker portion within circle VI in Fig. 4. Two teeth 10 with their two neighbouring different

slopes 70, 71 are in engagement with the nose 26, which preferably has a complementary form to the groove 72 which is formed by the slopes of adjacent teeth 10, therefore blocking the movement of the rod 5 in one direction and allowing said movement in the other direction.

The embodiment according to Fig. 1 to 4 is not the only possibility to achieve such advantageous handling of a forceps. Fig. 7 is a view in side elevation of a forceps 41 according to a second embodiment of the invention with the locking device in an open setting. All features within the embodiment of Fig. 7 having similar features within the embodiment according to Fig. 1 have the same reference numerals. Fig. 8 show an enlarged view of the lever portion within circle VI in Fig. 7 and Fig. 9 is an enlarged view of the locking portion within circle VII in Fig. 7. Within this embodiment a release button 42 is provided in parallel to one handle 12. The principle of the forceps 41 is as follows. A cylindrical locking element 35 is provided on or integral to handle 2. This locking element 35 comprises at least a rough surface, preferably comprising small transversal grooves 36. A complementary locking element 37 is provided with the release button 42 being realised as a lever arm extending in parallel to handle 12. The complementary locking element 37 comprises grooves or teeth 36 which are arranged along a curve with a changing curvature, i.e. the radius of curvature becomes greater between the position of the element 37 which is named the open setting in relationship to the position which is named the closed setting.

The open setting of Fig. 7 is achieved through a biased spring 28 extending between one end point 27 inside a lengthy slit between two webs 14' and 24' and another endpoint 57 near the pivoting point 33. In order to achieve the closed setting as shown

in Fig. 10 showing a view in side elevation of the forceps 41 according to Fig. 7 with the locking device in an closed setting, and as the detailed view of Fig. 11, an enlarged view of the lever portion within circle IX in Fig. 10, and Fig. 12, an enlarged view of the locking portion within circle X in Fig. 10. Through a pivoting of the lever 42 away from the handle 12 the two complementary surfaces 35 and 37 mutually engage and through the special form of the surface 37 the forceps 41 can not open anymore since the spring 28 now urges the lever 42 in the second stable setting, the closed setting.

Finally Fig. 13 shows a view in side elevation of a forceps 61 according to a third embodiment of the invention with the locking device in an open setting, and Fig. 14 shows a view in side elevation of the forceps 61 according to Fig. 13 with the locking device in a closed setting.

On the inner side of handle 2, a shaped rod 5 is swivel-mounted by means of a pin 6. The guiding bore 8 within the second handle 12 accepts the rod 5. The rod 5 comprises a number of catching elements 50. These may comprise grooves in a transversal direction to the longitudinal axis of the slightly curved rod 5. The rod 5 is preferably slightly curved, having a radius of curvature equivalent to the distance from the pivot point 3. The grooves or notches (=catching elements 10) are provided on the inside of the rod 5, i.e. directed towards the pivot point 3. Within the second handle 12 is located a bolt 48, which is pushed in direction of the rod 5 through a spring 47 which may be a disk spring and which is placed in the second handle 12 between the bolt 48 and the pivot point 3 acts to move surface 46 of rod 5 towards surface 46 of an element 37. In the open setting shown in Fig. 13 the surfaces 46 of element 37 and rod 5 are not in engagement, whereas in Fig. 14 the element 37 is

pushed inside the forceps 61 therefore bringing the surfaces 46 in contact one to another achieving the same function as within the second embodiment, i.e. preventing the jaws 4 from opening but allowing closure. The arrangement according to Fig. 13 and 5 12 allows a further compression, just gliding the surfaces 46 one against another. However, there is no backwards travel, which can only be achieved through pushing the element 37 towards the outside through pushing the nose 49 in either direction (from Fig. 13 to Fig. 14 and vice versa).

10

In all embodiments the release or fixation element is directly usable when gripping the forceps, either through manipulation within the fingerholes 32 as in the first embodiment, or through a release lever 42 in parallel to the handle as in the second 15 embodiment, or through a bolt 48 releasing element, provided in parallel to the second handle as in the third embodiment.

One of the advantages of the embodiment according to Fig. 1 is the possibility to switch from the open to the closed setting 20 through movement of the handles. There is no additional button or lever to be manipulated. Therefore the surgeon can switch the device into the closed setting, engage the device within the body to be gripped, close the jaws 4 further, while within this closed setting the surgeon is sure that one position of the jaws 25 reached they will not open any more. If now the grip has to be loosened, the surgeon can switch from the closed setting to the open setting without leaving the gripping holes of the handles. Then he opens the jaws and continue to work on the same body to be gripped or another without losing time.

30

The second advantage of the embodiment shown in Fig. 7 to 10 is the reduced space requirement and the button 49 is still easily reached since mounted in a natural position for the hand. This

result can be reached through the definition of the surfaces 36 within the elements 35 and 37, respectively. In the figures one element has a cylindrical curvature while the other has a changing radius of curvature. In the open setting (freely movable
5 jaws 4) the two elements are in a small distance one from another when the distance is measured on the straight line between the two axes. When the button 42 is moved to the closed setting, the element 37 is rotated around the axis 33. Therefore the distance changes and eventually becomes zero. The surfaces 36 are
10 engaging one another. When the surgeon now would try to open the jaws, i.e. move the second handle 2 away from the first handle 12, the two surfaces would rotate around the axes 33 and 3, respectively. But this rotation would diminish further the distance between said surfaces since one of the elements has a
15 growing radius of curvature in this direction of rotation resulting in a blocking state. The further closing of the jaws through movement of the handles would move the elements in a direction where at least one element has a diminishing radius of curvature thus allowing this movement.

20

In order to ensure the best engagement of the surfaces they are provided with microgrooves or grooves in a direction perpendicular to the drawing sheets.

Claims

1. An orthopaedic ratcheting forceps, especially for fixation
5 of fractures, with two handles (2, 12), wherein a first catching
element (5 or 35) is mounted pivotally with one handle (2 or
12), wherein a complementary catching element (26 or 37) is
mounted on the other handle (12 or 2), wherein the catching ele-
10 ments (26, 27) can assume only two stable settings which can be
switched with a single hand, one closed setting within which the
jaws (4) of the forceps can only be further closed and an open
setting within which the handles (2, 12) of the forceps are
freely movable, so that the forceps can be opened as well as
15 closed, characterised in that a spring means (28; 47) is pro-
vided in one handle (12), said spring means (28; 47) is biased
between two mounting points, a lever end (25; 58; 49) connected
with one of the catching elements (26; 37) engages the spring
means (28; 47) and through movement of an activation element
(32; 42; 49) the lever end (25; 49) is switchable between the
20 closed setting and the open setting.

2. The forceps according to claim 1, wherein the activation
element is the one handle (12) which is pivotable.

25 3. The forceps according to claim 1 or 2, wherein the spring
means is a leaf spring (28) mounted within the one handle (12)
or wherein the spring means is a part of said one handle (12)
having a memory effect allowing for the two settings.

30 4. The forceps according to claim 3, wherein said spring (28)
is mounted between abutting side walls (14, 24) within said han-
dle (12).

5. The forceps according to claim 4, wherein said one handle (12) comprises two portions (22, 32) hinged together at a pivoting point (13), wherein said pivoting point is the second mounting point (13) of the spring (28) and wherein said spring (28) is confined between two, especially convex, side walls (14, 24) of the jaws portion (22) of the two portions (22, 32) and the prolongation of the fingerhole portion (32) of the two portions (22, 32) forms the lever end (25) and engages the leaf spring (28).

10

6. The forceps according to claim 5, wherein said first catching element is a rod (5) mounted pivotally on the other handle (2), the rod (5) extending through an opening (8) within the fingerhole portion (32) and having grooves (10) on the side directed towards the jaws (4) of the forceps and wherein the grooves (10) of the rod (5) can be engaged through the complementary catching element formed as a nose (26) extending from said fingerhole portion (32).

7. The forceps according to claim 6, wherein said rod (5) is prebiased in direction of the jaws (4) of the forceps through a spring (7) pushing the rod (5) in the direction of the grooves (10) on the side directed towards the jaws (4).


8. The forceps according to claim 1, wherein the second mounting point (57) is the point of engagement of the lever end (58) which can be switched between the two side walls (14, 24) of the first handle (12).


9. The forceps according to claim 8, wherein the catching elements (35) and the complementary catching elements (37) are curved elements wherein at least one catching element (35 or 37) has a changing radius of curvature, in order to provide, in the


closed setting - a blocking device upon contact of the surfaces (36) of the catching elements (35 and 37) against further movement in the direction of opening the forceps.

5 10. The forceps according to claim 1, wherein said first catching element is a rod (5) mounted pivotally on the other handle (2), the rod (5) extending through an opening (8) within the handle (12) and having grooves (50) on the side directed towards the jaws (4) of the forceps and wherein the grooves (50) of the
10 rod (5) can be engaged through the spring (47).


11. The forceps according to claim 10, wherein the complementary catching element (37) is part of the activation element (49) comprising the complementary catching elements (37) which can be
15 pushed inside said opening (8) within the handle (12) to disengage the spring (47) from the rod (5).









4/6







INTERNATIONAL SEARCH REPORT

International Application No

PCT/CH 03/00718

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/28 B25B7/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B B25B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 89 06939 A (PFIZER HOSPITAL PRODUCT GROUP) 10 August 1989 (1989-08-10) cited in the application	1
A	page 4, line 23-37; figures 6-9	9
X	DE 93 14 581 U (WOLF GMBH RICHARD) 25 November 1993 (1993-11-25)	1, 10
A	claims 1-3; figure 1 page 8, line 8-30	9
X	US 4 538 485 A (SAILA TAUNO) 3 September 1985 (1985-09-03)	1
A	claim 1; figures 2,3	9
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 January 2004

Date of mailing of the International search report

23/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Macaire, S

INTERNATIONAL SEARCH REPORT

International Application No

P H 03/00718

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 176 702 A (SMITH KEVIN W ET AL) 5 January 1993 (1993-01-05) abstract; figures 1B,10,10E column 10, line 59 -column 11, line 4 column 12, line 44-68 ---	1,3,9
A	US 5 373 866 A (WHALEN II JOHN R) 20 December 1994 (1994-12-20) abstract; figures 1,3,4 column 5, line 15-24 ---	1,9
A	DE 20 25 868 A (FA. WALTERS PETERS) 9 December 1971 (1971-12-09) page 1, paragraph 1; figure 1 page 3 ---	1,2,5,6, 9
A	DE 28 49 009 A (LANDANGER LOUIS) 28 June 1979 (1979-06-28) column 6, paragraph 3 -column 7, paragraph 1; claim 1; figures 1,2 ---	1,3,9
A	DE 100 49 379 A (STORZ MARTIN) 11 April 2002 (2002-04-11) abstract; figures 1,3 ---	1,2,5,6, 9
A	DE 242 254 C (LOUIS & H. LOEWENSTEIN) 3 January 1912 (1912-01-03) column 1, line 1-17; figures 1,2 ---	2,5,9
A	DE 91 09 113 U (KOTHE) 6 February 1992 (1992-02-06) page 6, paragraph 2; figures 1,2 -----	1,3,9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CH 03/00718

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 8906939	A	10-08-1989	US 4896661 A	30-01-1990
			AT 105697 T	15-06-1994
			CA 1302827 C	09-06-1992
			DE 68915436 D1	23-06-1994
			DE 68915436 T2	01-09-1994
			EP 0393151 A1	24-10-1990
			ES 2017118 A6	01-01-1991
			WO 8906939 A1	10-08-1989
DE 9314581	U	25-11-1993	DE 9314581 U1	25-11-1993
US 4538485	A	03-09-1985	NONE	
US 5176702	A	05-01-1993	US 5192298 A	09-03-1993
			US 5171258 A	15-12-1992
			AT 162382 T	15-02-1998
			AU 655528 B2	22-12-1994
			AU 3283193 A	12-08-1993
			AU 3605893 A	03-09-1993
			CA 2088869 A1	07-08-1993
			DE 69316401 D1	26-02-1998
			DE 69316401 T2	27-08-1998
			EP 0555103 A1	11-08-1993
			IL 104591 A	14-11-1996
			JP 2573781 B2	22-01-1997
			JP 6014874 A	25-01-1994
			WO 9315673 A1	19-08-1993
			AU 647349 B2	17-03-1994
			AU 1404492 A	08-10-1992
			CA 2065089 C	07-02-1995
			DE 69222216 D1	23-10-1997
			DE 69222216 T2	19-03-1998
			EP 0507622 A1	07-10-1992
			IL 101493 A	31-10-1995
			JP 2573771 B2	22-01-1997
			JP 5091974 A	16-04-1993
			US 5507297 A	16-04-1996
			US 5443480 A	22-08-1995
			US 5396900 A	14-03-1995
			US 5395386 A	07-03-1995
			US 5392789 A	28-02-1995
			US 5439478 A	08-08-1995
			US 6041679 A	28-03-2000
			US 5203785 A	20-04-1993
			US 5258004 A	02-11-1993
			US 5215101 A	01-06-1993
			US 5269804 A	14-12-1993
			US 5170800 A	15-12-1992
			US 5174300 A	29-12-1992
			US 5331971 A	26-07-1994
			US 5241968 A	07-09-1993
			US 5320636 A	14-06-1994
			US 5293878 A	15-03-1994
			AU 655327 B2	15-12-1994
			AU 2715292 A	22-04-1993
			CA 2080994 A1	22-04-1993
			EP 0542437 A1	19-05-1993
			IL 103484 A	08-12-1995

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 03/00718

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5176702	A		JP 2573777 B2 JP 6054802 A	22-01-1997 01-03-1994
US 5373866	A	20-12-1994	NONE	
DE 2025868	A	09-12-1971	DE 2025868 A1	09-12-1971
DE 2849009	A	28-06-1979	FR 2411601 A1 DE 2849009 A1	13-07-1979 28-06-1979
DE 10049379	A	11-04-2002	DE 10049379 A1	11-04-2002
DE 242254	C		NONE	
DE 9109113	U	19-12-1991	DE 9109113 U1 EP 0513471 A2 US 5290309 A	19-12-1991 19-11-1992 01-03-1994

Box No. VIII (iii) DECLARATION: ENTITLEMENT TO CLAIM PRIORITY

The declaration must conform to the standardized wording provided for in Section 213; see Notes to Boxes Nos. VIII, VIII(i) to (v) (in general) and the specific Notes to Box No. VIII (iii). If this Box is not used, this sheet should not be included in the request.

Declaration as to the applicant's entitlement, as the international filing date, to claim the priority of the earlier application specified below, where the applicant who filed the earlier application or where the applicant's name has changed since the filing of the earlier application (Rules 4.17(iii) and 51bis.1(a)(iii)):

In relation to this international application

Stryker Trauma SA is entitled to claim priority of earlier application No. 02 405 938.8 by virtue of the following:

- (viii) the applicant's name changed from Stryker Trauma – Selzach AG to Stryker Trauma SA on April 30, 2003
- (ix) this declaration is made for the purposes of all designations.

☐ This declaration is continued on the following sheet, "Continuation of Box No. VIII (iii)".